Jäger Plus

HIGH PERFORMANCE MONOCRYSTALLINE PERC MODULE



RSM144-6-390M-410M

144 CELL
Mono PERC Module

390-410Wp
Power Output Range

1500VDC
Maximum System Voltage

20.4%
Maximum Efficiency

KEY SALIENT FEATURES

- Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing
- Industry leading lowest thermal co-efficient of power
- Industry leading 12 years product warranty
- Excellent low irradiance performance
- Excellent PID resistance
- Positive tight power tolerance
- Dual stage 100% EL Inspection warranting defect-free product
- Module Imp binning radically reduces string mismatch losses
- Warranted reliability and stringent quality assurances well beyond certified requirements
- Certified to withstand severe environmental conditions
  - Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
  - Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
  - Excellent mechanical load 2400Pa & snow load 5400Pa resistance

ISO9001
ISO14001
OHSAS18001
IEC TS 62941

RISEN ENERGY CO., LTD.

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

Tashan Industry Zone, Meilin, Ninghai 315609,Ningbo | PRC
Tel: +86-574-59953239 Fax: +86-574-59953599
E-mail: marketing@risenenergy.com Website: www.risenenergy.com

risen solar technology

LINEAR PERFORMANCE WARRANTY

12 year Product Warranty / 25 year Linear Power Warranty



Dimensions of PV Module

Unit: mm







Our Partners:

ELECTRICAL DATA (STC)

Model Number	RSM144-6-390M	RSM144-6-395M	RSM144-6-400M	RSM144-6-405M	RSM144-6-410M
Rated Power in Watts-Pmax(Wp)	390	395	400	405	410
Open Circuit Voltage-Voc(V)	48.30	48.45	48.60	48.75	48.90
Short Circuit Current-Isc(A)	10.30	10.40	10.50	10.60	10.70
Maximum Power Voltage-Vmpp(V)	40.25	40.35	40.45	40.55	40.65
Maximum Power Current-Impp(A)	9.70	9.80	9.90	10.00	10.10
Module Efficiency (%)	19.4	19.7	19.9	20.2	20.4

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA (NMOT)

Model Number	RSM144-6-390M	RSM144-6-395M	RSM144-6-400M	RSM144-6-405M	RSM144-6-410M
Maximum Power-Pmax (Wp)	291.8	295.6	299.3	303.1	306.9
Open Circuit Voltage-Voc (V)	44.40	44.60	44.70	44.90	44.99
Short Circuit Current-Isc (A)	8.45	8.53	8.61	8.69	8.77
Maximum Power Voltage-Vmpp (V)	36.90	37.00	37.05	37.14	37.24
Maximum Power Current-Impp (A)	7.92	8.00	8.08	8.16	8.24

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Monocrystalline, 9BB
Cell configuration	144 cells (6×12+6×12)
Module dimensions	2015×996×40mm
Weight	23kg
Superstrate	3.2 mm, High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy type 6063T5, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm² (12AWG), Positive(+)270mm, Negative(-)100mm
Connector	Risen Twinsel PV-SY02, IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	45°C±2°C
Temperature Coefficient of Voc	-0.29%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.37%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	20A
Limiting Reverse Current	20A

PACKAGING CONFIGURATION

	40ft	20ft
Number of modules per container	594	270
Number of modules per pallet	27	27
Number of pallets per container	22	10
Packaging box dimensions (LxWxH) in mm	2040×1130×1130	2040×1130×1130
Box gross weight[kg]	670	670

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2019 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.