
Ultracell®

'Quality in Every Language'

LIT75-12


12V 75Ah/960Wh


Lithium Series






Technical Dimensions (mm)







Ultracell (UK) Ltd | Vesty Business Park, Vesty Road, Liverpool, L30 1NY, United Kingdom
Tel: +44 (0) 151 523 2777 | Fax: +44 (0) 151 523 0855 | Email: info@ultracell.co.uk
www.ultracell.co.uk

LIT-V1-REV2 08/20
ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE

Ultracell®
'Quality in Every Language'

TechData


LIT75-12
12V 75Ah/960Wh
Lithium Series

Image



Terminal Dimensions (mm)

Standard
Terminal: F6



Technical Specification

Output	Nominal Voltage	12.8V
	Nominal Capacity	75Ah
	Energy	960Wh
Terminal Type	Standard Terminal	F6
Container Material	Standard Option	ABS
	Flame Retardant Option (FR)	ABS (UL94:VO)
	IP Class	IP65
Standard Charge	Charge Voltage	14.6±0.2V
	Charge Mode	0.2C (CC) charge to 14.6V, then charge (0.02C) (CV)
	Charge Current	40A
	Max. Charge Current	75A
	Standard Charge Current	14.6V ± 0.2V
Standard Discharge	Rated Discharge Current	38A
	Max. Discharge Current	75A
	Discharge Cut-off Voltage	10V
Internal Resistance	≤50mΩ	
Discharge Characteristics	Operating Temp Range	Charge: 0 ~ 55°C Discharge: -20 ~ 60°C Storage: -20 ~ 45°C
Efficiency of Charge	100% @0.5C	
Efficiency of Discharge	96~99% @1C	
Cycle Life	≥2000 cycles @ 1C 100%DOD	
Battery Management System	Complete with BMS unit measuring current, voltage, single cell surface temperature and the ambient temperature of the battery.	

Self Discharge

Ultracell® LIT batteries may be stored for up to 2 years at 25°C and then a refresh charge is required. For higher temperatures the time intervals will be shorter.

Transportation

Ultracell® LIT Batteries will be at 30% State of Charge when shipped in accordance to the applicable international and national government regulations. To prevent damage during transit, ensure packaging is safe and secure. Keep battery dry and away from direct sunlight. Suitable for all transportation vehicles.

VdS
MH 29410
EMC 1188-C
IEC 60896
ISO 9001:2015

Ultracell (UK) Ltd | Vesty Business Park, Vesty Road, Liverpool, L30 1NY, United Kingdom
Tel: +44 (0) 151 523 2777 | Fax: +44 (0) 151 523 0855 | Email: info@ultracell.co.uk
www.ultracell.co.uk


LIT-V1-REV2 08/20
ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE

Ultracell®
'Quality in Every Language'


TechData

LIT75-12
12V 75Ah/960Wh
Lithium Series


Different Rate Discharge Curve (25°C)




Different Temperature Discharge Curve (0.5C)




State of Charge Curve (0.5C, 25°C)




Charging Characteristics (0.5C, 25°C)



Cycle Life on D.O.D (25°C)



Temperature on Self Discharge Curve



MH 29410

EMC 1188-C

IEC 60896

ISO 9001:2015

Ultracell (UK) Ltd | Vesty Business Park, Vesty Road, Liverpool, L30 1NY, United Kingdom
Tel: +44 (0) 151 523 2777 | Fax: +44 (0) 151 523 0855 | Email: info@ultracell.co.uk
www.ultracell.co.uk

LIT-V1-REV2 08/20
ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE